







## Accessories

A full range of accessories is available to enhance installation, operation and maintenance of the 1830/1840 Series as listed below:

- STE moistureproof sensor termination enclosure (202-034-01)
- Slimline sink weight Ø17.5 mm (DA2608-1-01)
- Short sink weight Ø25 mm (DA4068-1-01)
- Cable clamp system (192-373-01)
- 360° Rotatable calibration adaptor to:  
G1/8 (DA4112-1-01) 1/8 NPT (DA4112-2-01)
- Economical direct calibration adaptor to:  
G1/8 (DA2537-1-01) 1/8 NPT (DA2537-2-01)
- Accessory pack contains (S01830E)  
STE box                      Slimline sink weight  
Cable clamp                 Direct calibration adaptor

## Options

### (A) Lightning Surge Arrestor (PTX 1830/1840 only)

Integral lightning protection assembly certified to standard IEC 61000-4-5 (level 4).

### (B) Intrinsically Safe Version

### (C) Alternative Pressure Connection

In place of the standard acetyl nose cone, a welded male pressure connection can be supplied.

### (D) Improved Accuracy

An improved accuracy of  $\pm 0.06\%$  FS BSL is available ( $\pm 0.08\%$  FS BSL for ranges below 1 mH<sub>2</sub>O (1.5 psi))

## Ordering Information

Please state the following:

- (1) Select model number
- (2) Pressure range and scale units
- (3) Options (if required)
- (4) Cable length required
- (5) Accessories (order as separate items).
- (6) Supporting Services (order as separate items)

Code	Model	Code	Cable type
PDCR18	mV output	3	Polyurethane
PTX 18	mA output	4	Hytrel® 6108
		0	Code Not used

↓                      ↓                      ↓

— — — — —